

wherein the one or more conductive tracks terminate at or near an edge of the modular printed circuit film element,

- molding an insulative material over the stacked assembly of modular printed circuit film elements to constitute a rigid block,

- cutting the rigid block laterally along the stacked assembly to expose an end for each of the one or more conductive tracks at a common alignment level and so that the exposed ends from the plurality of modular printed circuit film elements are flush with a surface of one face of the block, which ^{the} cutting step is performed at least once, and

- creating connections on the one face of the block with which the exposed ends are flush to selectively interconnect the one or more conductive tracks and to connect the one or more conductive tracks to connection means external to the module.

Claim 8. (Amended) A method of obtaining a module, comprising the steps of:

- providing a first support and a second support;

- forming at least a first conductive track having turns on the first support to form a winding thereon, wherein the first conductive track terminates at or near an edge of the first support;

- forming at least a second conductive track having turns on the second support to form a winding thereon, wherein the second conductive track terminates at or near an edge of the second support;

- stacking the first support on top of the second support to form a stacked assembly;

- molding an insulative material over the stacked assembly to form a block; *then*

cutting the block laterally along the stacked assembly to expose respective ends of the first and second conductive tracks at a common alignment level and so that the exposed ends are flush with one face of the block; and

interconnecting the conductive tracks on the one face of the block.

Sub D2

~~Claim 9. (Amended) The method claimed in claim 8, further comprising the steps of:
providing a supplementary support that carries an electrical component and that has a
conductive track terminating at or near an edge of the supplementary support;
prior to molding the insulative material over the stacked assembly to form a block,
stacking the supplementary support with the first support and the second support so that the
stacked assembly includes the supplementary support, the first support, and the second support,
and so that the step of cutting the block laterally along the stacked assembly exposes respective
ends of the conductive tracks on the supplementary support, the first conductive tracks and the
second conductive tracks at the common alignment level and so that the respective exposed ends
are flush with one face of the block.~~

C2
